

Alternative D and E:

It is anticipated that the Tribe would pay a fair share of the costs for apparatus within the District's apparatus replacement program and staffing needs.

### **Ambulance Service Agreement**

**Measure 5.10-5:** The Tribe would enter into a service contract with the Cloverdale Healthcare District for provision of ambulance services to the project site.

### **Emergency Response Plan**

**Measure 5.10-6:** The Tribe would develop an emergency response plan (emergency medical, pandemic, natural disaster, failure of private water/wastewater facilities if applicable) in coordination with the local fire protection and emergency medical service providers. The plan would address staff training and the necessity of an on-site defibrillator.

## **5.11 Noise**

The following mitigation measures are recommended for Alternatives A, B, C, D, and E:

**Measure 5.11.1a:** Construction activities shall be limited to the daytime hours of 7:00 a.m. to 6:00 p.m Monday through Friday, and shall be prohibited weekends and holidays.

**Measure 5.11.1b:** To reduce daytime noise impacts due to construction, the applicant shall require construction contractors to implement the following measures:

- Equipment and trucks used for construction shall use the industry standard noise control techniques (e.g., standard mufflers, equipment redesign, use of intake silencers, ducts, engine enclosures, and acoustically-attenuating shields or shrouds).
- Stationary noise sources shall be located as far from adjacent receptors, whenever feasible, and they shall be muffled and enclosed within temporary sheds and incorporate insulation barriers or other measures.

**Measure 5.11.2:** Rooftop air conditioners and other continuously operated 24-hour equipment (i.e., rooftop chillers, refrigeration systems, and exhaust fans) shall be located at the furthest away point from the nearest residential receptor and/or include additional noise attenuation (i.e., rooftop barriers or parapets between the equipment and the nearest sensitive receptor to absorb or deflect the noise) as necessary to reduce noise levels from the equipment to below 50 dBA at the nearest off-site sensitive receptors.

## **5.12 Hazardous Materials**

The following mitigation measures are recommended for Alternatives A, B, C, D, and E: